

TECHNICAL DATA SHEET

UHPD 10w/30 E9

Product Description:

UHPD 10w/30 E9 is a heavy duty diesel engine oil incorporating an advanced mid-SAPS additive package which has been formulated to meet the demands of the Euro 5 emissions requirements. UHPD 10w/30 E9 provides maximum protection even when operating under very severe conditions and is suitable for engines with Selective Catalytic Reduction systems and Diesel Particulate Filters.

Benefits:

- Offers improved wear protection and soot dispersancy
- Wide range of applications
- Extended drain intervals
- Protects after-treatment systems

Applications:

UHPD 10w/30 E9 is suitable for use in Euro 5 and some Euro 6 engines diesel engines. Equipment manufactures include Mercedes Benz, MAN, DAF, Renault and Volvo.

Product Profile:

API: CJ-4
ACEA: E9
Cummins: CES 20071, CES 20081
CAT: ECF-3
JASO: DH-2
Mack: EO-O Premium Plus
MAN: M3575
Mercedes Benz: 228.31
Renault: RLD-3
Volvo: VDS-4

Typical Test Data:

| | | |
|---------------------------|---|-------|
| Specific Gravity @ 15°C | - | 0.867 |
| Kinematic Viscosity (cSt) | | |
| @100°C | - | 11.8 |
| @40°C | - | 78 |
| Viscosity Index | - | 145 |
| Flash Point (Closed) °C | - | 210 |
| Pour Point °C | - | -35 |
| TBN | - | 9.5 |
| Sulphated Ash %Wt | - | 1.0 |

