

TECHNICAL DATA SHEET

SYNTHETIC C4 5W/30

Product Description:

0214

Synthetic C4 5W/30 is a low SAPS (Sulphated Ash Phosphorus and Sulphur) fully synthetic multigrade engine oil. Low SAPS additive technology ensure optimum performance of emission control equipment including diesel particulate filters (DPF) and Three Way Catalyst (TWC). The additive technology also provide long term emission system protection, ensuring a high level of constant pollution control thereby minimising environmental damage and long term wear protection.

Benefits:

- Effective environmental protection
- Ensures lubricant performance over extended drain periods
- Effective fuel efficiency
- Very high standards of engine cleanliness
- Long term anti-wear and oxidation stability
- Excellent high and low temperature performance
- Long term additive performance

Applications:

Synthetic C4 5W/30 is suitable for use in petrol and diesel engines including turbocharged engines.

Product Profile:

ACEA: C4
Mercedes Benz: 226.51
Renault: RN0720

Typical Test Data:

KV @ 100°C (cSt)	-	11.8
KV @ 40°C (cSt)	-	67.3
Viscosity Index	-	165
Pour point (°C)	-	-45
Sulphated ash (% w/w)	-	0.4
TBN (mg KOH / g)	-	7.0
Flash Point COC (°C)	-	212